

segment let's say this is my code let's say there is a code with the name `harry.c` now this code will be first loaded into my main memory I told you what is the first thing that happens? then it will come to this line it will come to `fun1 ( )`, it will execute `fun1 ( )`. `fun2 ( )` is calling inside `fun1 ( )` now the variables that I had created inside it will be created here let's say I have created `k` & `l` let me write here : initialize `k` and `l` and after that I'm calling `fun2 ( )` so as soon as `fun2 ( )` will be called it will say to `fun1 ( )` that you wait for a while, I call `fun2 ( )` and be back by fetching the value whatever it will return `fun1 ( )` replied that you go and get it call `fun2 ( )` and get its value.

me where do I give the milk to the milkman because the pointer will store the address of the malloced memory so the milkman will get the milk from the pointer and the pointer will stay there until you return the function or until you delete [it.it](http://it.it) will say to `fun1 ( )` that you're coming back and now you can start your execution again. If anyone asks you this question, that why heap is used, it can also be done from stack. So that thing is done here with the help of dynamic memory because when does the stack of a function end it ends when the function is returned. I just come back with the value you just wait here. You go and get it and then what will happen, `fun` function will be called.

this video we will focus on linked list & binary search tree so if you want to know more about these then you should go ahead and watch the video and learn more about these things. If you still think that you want to do all of these things with Python, then I am saying that when you will go for an interview, the person in front of you will expect C, C++, or Java from you. If you don't know C properly, then I have made a 15-hour long video of C with notes.

Preview from Notesale.co.uk  
Page 2 of 2